

### DUNLOP KART TYRE RANGE FOR 2011-2013

		Tyre Size	Pattern	Tread Compound																		RIM WIDTH(inch)		Outer Diam. (mm)	Tyre Width (mm)	Tread Width (mm)		
				DFK2	SL1	SL3	SL4	SL5	SL9	SL6	R6	RH2	DDH	DDM	DDS	DEH	DEM	DES	SLW1	SLW2	KT3 RAC	W12	Range				Standard	
For	Front Tyre	10X3.60-5	SLICK		○	○																	3.5 - 5	4	252	117	73	
		10X4.50-5	SLICK	○	○	○	○					○												4 - 5.5	4,5	255	133	86
		10X4.50-5	SLICK					○	○	○														4 - 5.5	4,5	262	130	105
		10X4.50-5	SLICK												⊙	⊙	⊙							4 - 5.5	4,5	263	130	108
		11X5.00-5	SLICK														○							4 - 5.5	4,5	264	136	96
		11X5.50-5	SLICK				○										○							4.5 - 6	6	264	165	115
		11X5.00-6	SLICK											○	○		○							4 - 5.5	4,5	267	134	100
		11X5.50-6	SLICK											○										4.5 - 6	6	273	161	115
	Rear Tyre	11X5.50-6	SLICK													○			⊙*				4.5 - 6	6	282	161	115	
		11X5.00-5	SLICK			○																	4 - 5.5	4,5	268	136	96	
		11X6.00-5	SLICK				○																5 - 7	6	273	170	112	
		11X6.00-5	SLICK														○						5 - 7	6	278	165	115	
		11X6.50-5	SLICK	○																			6 - 8	6,5	285	181	124	
		11X6.50-5	SLICK													○	○	○					6 - 8	6,5	278	178	130	
		11X7.10-5	SLICK	○	○	○	○																7 - 8.5	8	280	210	136	
		11X7.10-5	SLICK					○	○	○													7 - 8.5	8	278	209	155	
Wet Tyre	11X7.10-5	SLICK													⊙	⊙	⊙					7 - 8.5	8	276	210	160		
	11.5X6.00-6	SLICK													○	○						5 - 7	6	280	165	120		
	11.5X7.10-6	SLICK												○		○						7 - 8.5	8	283	210	155		
	11.5X8.00-6	SLICK													○	○						7 - 9	9	286	232	165		
	11.5X8.00-6	SLICK																⊙*				7 - 9	9	289	233	170		
	For	Front Tyre	10X3.60-5	KT3																		○	3.5-4.5	4	258	120	78	
10X4.50-5			KT12																		○	4 - 5.5	4,5	255	130	112		
10X4.50-5			KT13																		⊙	4 - 5.5	4,5	262	130	115		
10X4.00-5			KT6														○						4 - 4.5	4	260	120	80	
11X5.00-6			KT6																		⊙*	4 - 5	4,5	278	132	100		
Rear Tyre		11X4.50-5	KT3																		○		4-5	4,5	275	140	94	
		11X6.00-5	KT3																		○		5-7	6	284	166	116	
		11X6.50-5	KT12																		○		6 - 8	6,5	270	177	130	
		11X6.50-5	KT13																		⊙		6 - 8	6,5	280	175	125	
		11X6.50-5	KT6														○						6 - 8	6,5	274	179	136	
11.5X7.10-6	KT6																		□*		7 - 8.5	8	290	208	155			

□ : HOMOLOGATED BY CIK    ⊙\* : SuperKart(250cc)    ○ : NON-CIK

R6 ONLY ONE SIZE FOR FRONT OF OVAL TRACK RACE, SL-TYPE PROFILE AND HIGH GRIP COMPOUND(SIMILAR TO SOFT)

SL6 SAME COMPOUND AS SL4, BUT SIMILAR PROFILE AND DIMENSION TO HIGH-GRIP TYRE

SL9 MIDDLE POSITION BETWEEN SL5 AND SL6

Soft : SL6 = SL4 > SL9 > SL5 = SL3 > SL1 > DFK2: Hard

SLW1 LONG LIFE WET TYRE

SLW2 MEDIUM RANGE FOR WET (BETWEEN SLW1 AND W12)

DEH HARD RANGE OF HIGH GRIP COMPOUND

DEM MEDIUM RANGE OF HIGH GRIP COMPOUND

DES SOFT RANGE OF HIGH COMPOUND

W12 SOFTER THAN W11